


SEMILUNA SR.L1.S200.XY

Type: wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61) or RAL Bronze (.73)

Colour: RAL9003 (60); RAL9005 (61); RAL Bronze (73)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CORR	IK	BT	TS	Weight
6,3	3000	992	595	340	200	250	L	-	-	-	-	-	3200

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 6,3 W

Color temperature: 3000 K

Module luminous flux: 992 lm

Luminaire luminous flux: 595 lm

A: 340 mm

B: 200 mm

C: 250 mm

Dali 1: Available

Dali 2: Not available

Corridor function: Not available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Weight: 3200 g

Lucis SR.L1.S200.X SEMILUNA LED / LDC (Polar)

Luminaire: Lucis SR.L1.S200.X SEMILUNA LED
Lamps: 1 x LED G5

