



POLARIS S.P BS14.P1.200.XY

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
11	3000	1656	1446	200	140	210	M	-	-	Q*	-	2000

Lucis BS14.P1.200.X POLARIS S.P LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 11 W

**Color temperature:** 3000 K

**Module luminous flux:** 1656 lm

**Luminaire luminous flux:** 1446 lm

**A:** 200 mm

**B:** 140 mm

**C:** 210 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 2000 g

Luminaire: Lucis BS14.P1.200.X POLARIS S.P LED  
Lamps: 1 x LED G6

