


POLARIS S.P BS19.P3.280.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
16,8	3000	2460	2148	280	190	285	M	-	-	Q*	-	2500

Lucis BS19.P3.280.X POLARIS S.P LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16,8 W

Color temperature: 3000 K

Module luminous flux: 2460 lm

Luminaire luminous flux: 2148 lm

A: 280 mm

B: 190 mm

C: 285 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2500 g

Luminaire: Lucis BS19.P3.280.X POLARIS S.P LED
Lamps: 1 x LED G6

