



POLARIS S.P BS24.P1.350.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
28,5	3000	4044	3531	350	240	345	M	-	P*	Q*	-	3900

Lucis BS24.P1.350.X POLARIS S.P LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 28,5 W

Color temperature: 3000 K

Module luminous flux: 4044 lm

Luminaire luminous flux: 3531 lm

A: 350 mm

B: 240 mm

C: 345 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 3900 g

Luminaire: Lucis BS24.P1.350.X POLARIS S.P LED
Lamps: 1 x LED G6

