



OMNIA LR2.K1.02.X

**Typ:** Stehleuchte

**Lampenschirm:** Acrylglas

**Metallteile:** lackiertes Stahlblech RAL 9003 (.60), RAL 9005 (.61) oder RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 1	DALI 2	☀️	🏃	🔗	📄	👤
19,2	3000	2474	1920	680	370	1700	1250	-	-	-	-	-	-	12200

**Vorschalgerät:** Driver

**CRI:** >90

**LED-Lebensdauer:** L80/F10 50000 Stunden

**Watt:** 19,2 W

**Farbtemperatur:** 3000 K

**Module luminous flux:** 2474 lm

**Luminaire luminous flux:** 1920 lm

**A:** 680 mm

**B:** 370 mm

**C:** 1700 mm

**D:** 1250 mm

**:** Nicht Verfügbar

**Dali 2:** Nicht Verfügbar

**Bewegungsmelder:** Nicht Verfügbar

**Notlichtmodul:** Nicht Verfügbar

**Bluetooth-Steuerung:** Nicht Verfügbar

**Track-System:** Nicht Verfügbar

## Lucis LR2.K1.O2.X\_pc(2) OMNIA LED / LDC (Polar)

Luminaire: Lucis LR2.K1.O2.X\_pc(2) OMNIA LED  
Lamps: 1 x LED G5

