



OMNIA ZT2.12.K2.O2.XY

Type: luminaire suspendu

Abat-jour: verre acrylique

Les pièces métalliques: acier laqué RAL 9003 (.60), RAL 9005 (.61) ou RAL 7016 (.62)

Suspension: tube



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 1	DALI 2	CORR	Corridor	Movement	Bluetooth	Track system	Weight
13,4	4000	1930	1499	605	420	-	M	-	-	-	Q*	-	5000

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 13,4 W

Température Couleur: 4000 K

Module luminous flux: 1930 lm

Luminaire luminous flux: 1499 lm

A: 605 mm

C: 420 mm

Dali 1: Non disponible

Dali 2: Disponible

fonction Corridor: Non disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Poids: 5000 g

Lucis ZT2.12.K2.O2.X_pc(2) OMNIA LED / LDC (Polar)

Luminaire: Lucis ZT2.12.K2.O2.X_pc(2) OMNIA LED
Lamps: 1 x LED G5

