


OMNIA ZT4.K2.O2.XY

**Type:** luminaire suspendu

**Abat-jour:** verre acrylique

**Les pièces métalliques:** acier laqué RAL 9003 (.60), RAL 9005 (.61) ou RAL 7016 (.62)

**Suspension:** tube



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CORR	Person Icon	Person Icon	Bluetooth	Track System	Weight
29	4000	4008	3110	605	335	420	-	M	-	-	-	Q*	-	6500

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 29 W

**Température Couleur:** 4000 K

**Module luminous flux:** 4008 lm

**Luminaire luminous flux:** 3110 lm

**A:** 605 mm

**B:** 335 mm

**C:** 420 mm

**Dali 1:** Non disponible

**Dali 2:** Disponible

**fonction Corridor:** Non disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Poids:** 6500 g

Lucis ZT4.K2.O2.X\_pc(4) OMNIA LED / LDC (Polar)

Luminaire: Lucis ZT4.K2.O2.X\_pc(4) OMNIA LED  
Lamps: 1 x LED G5

