


IZAR C ZL4.IC.K1.440.91Y

- Type:** suspension lamp
- Lampshade:** acrylic glass
- Light body:** white painted steel plate
- Pendant:** steel wire suspension with a transparent cable



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | B   | C    | D   | DALI 1 | DALI 2 | CORR | Emergency | Motion | Bluetooth | Track | Weight |
|------|------|-------------------------|----------------------------|-----|-----|------|-----|--------|--------|------|-----------|--------|-----------|-------|--------|
| 37,7 | 3000 | 4448                    | 3 696                      | 440 | 440 | 2000 | 440 | -      | M      | N*   | -         | P*     | Q*        | -     | 8000   |

- Voltage:** 230V
- IK code:** IK06
- Ballast:** Driver
- CRI:** >90
- LED life:** L80/F10 50000 hours
- Watt:** 37,7 W
- Color temperature:** 3000 K
- Module luminous flux:** 4448 lm
- Luminaire luminous flux:** 3 696 lm
- A:** 440 mm
- B:** 440 mm
- C:** 2000 mm
- D:** 440 mm
- Dali 1:** Not available
- Dali 2:** Available
- Corridor function:** Available on inquiry
- Motion sensor:** Available
- Emergency module:** Available on inquiry
- Bluetooth control:** Available on inquiry
- Track system:** Available
- Weight:** 8000 g

Lucis ZL4.IC.K1.440.X IZAR C LED / LDC (Polar)

Luminaire: Lucis ZL4.IC.K1.440.X IZAR C LED  
Lamps: 1 x LED 252/160-G5

