


IZAR C ZL4.IC.K2.440.91Y

- Type:** suspension lamp
- Lampshade:** acrylic glass
- Light body:** white painted steel plate
- Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 1	DALI 2	CORR	Emergency	Motion	Bluetooth	Track	Weight
37,7	4000	4659	3872	440	440	2000	440	-	M	N*	-	P*	Q*	-	8000

- Voltage:** 230V
- IK code:** IK06
- Ballast:** Driver
- CRI:** >90
- LED life:** L80/F10 50000 hours
- Watt:** 37,7 W
- Color temperature:** 4000 K
- Module luminous flux:** 4659 lm
- Luminaire luminous flux:** 3872 lm
- A:** 440 mm
- B:** 440 mm
- C:** 2000 mm
- D:** 440 mm
- Dali 1:** Not available
- Dali 2:** Available
- Corridor function:** Available on inquiry
- Motion sensor:** Available
- Emergency module:** Available on inquiry
- Bluetooth control:** Available on inquiry
- Track system:** Available
- Weight:** 8000 g

Lucis ZL4.IC.K2.440.X IZAR C LED / LDC (Polar)

Luminaire: Lucis ZL4.IC.K2.440.X IZAR C LED  
Lamps: 1 x LED 252/160-G5

