

POLARIS ZK PE ZK.P2.600.XY PE


**Type:** suspension lamp

**Lampshade:** polyethylene opal PE

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

**Pendant:** white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
48,5	4000	7800	7176	600	2000	M	-	P*	Q*	-	8700

Lucis ZK.P2.600.X PE POLARIS ZK PE LED / LDC (Polar)

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 48,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 7800 lm

**Luminaire luminous flux:** 7176 lm

**A:** 600 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 8700 g

Luminaire: Lucis ZK.P2.600.X PE POLARIS ZK PE LED  
Lamps: 1 x LED G6

