

POLARIS ZT PE ZT.P3.600.XY PE

**Type:** luminaire suspendu

**Abat-jour:** polyéthylène opal PE

**Les pièces métalliques:** acier laqué RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chromé (.80), inox (.83) ou laiton (.84)

**Suspension:** tube

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	🚶	🚶➡	🔊	📄	👤	
55,7	3000	8480	7801	600	1000	M	-	P*	Q*	R*	-	8900

**Tension:** 230V

**Ballaste:** Driver

**IK code:** IK10

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 55,7 W

**Température Couleur:** 3000 K

**Module luminous flux:** 8480 lm

**Luminaire luminous flux:** 7801 lm

**A:** 600 mm

**C:** 1000 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Disponible sur demande

**Sádrokarton:** Non disponible

**Poids:** 8900 g

Lucis ZT.P3.600.X PE POLARIS ZT PE LED / LDC (Polar)

Luminaire: Lucis ZT.P3.600.X PE POLARIS ZT PE LED  
Lamps: 1 x LED G6

