

POLARIS ZL PE ZL1.P2.600.XY PE



**Type:** luminaire suspendu

**Abat-jour:** polyéthylène opal PE

**Les pièces métalliques:** acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

**Suspension:** câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	☺	☺	☺	☺	☺	☺
48,5	4000	7800	7176	600	2000	M	-	P*	Q*	R*	-	8700

**Tension:** 230V

**Ballaste:** Driver

**IK code:** IK10

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 48,5 W

**Température Couleur:** 4000 K

**Module luminous flux:** 7800 lm

**Luminaire luminous flux:** 7176 lm

**A:** 600 mm

**C:** 2000 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Disponible sur demande

**Sádrokarton:** Non disponible

**Poids:** 8700 g

Lucis ZL1.P2.600.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.600.X PE POLARIS ZL PE LED  
Lamps: 1 x LED G6

