

BOWL S0.K3.B45

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

The first glass ceiling and wall luminaire, triplex opal matt, with an invisible fixture in the shade of the luminaire allowing clean and direct compositions of opal glass with different types of materials.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Emergency	Exit	Bluetooth	Manual	Person	
9,8	3000	1540	1169	450	350	110	285	M	-	-	Q*	-	-	4900

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80F10>72000 hodin

Watt: 9,8 W

Color temperature: 3000 K

Module luminous flux: 1540 lm

Luminaire luminous flux: 1169 lm

A: 450 mm

B: 350 mm

C: 110 mm

D: 285 mm

Dali 2: Available

Motion sensor: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 4900 g

Project 1



Lucis S0.K3.B45 BOWL LED / LDC (Polar)

Luminaire: Lucis S0.K3.B45 BOWL LED
Lamps: 1 x LED G6

