

BOWL S0.K3.B50

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

The first glass ceiling and wall luminaire, triplex opal matt, with an invisible fixture in the shade of the luminaire allowing clean and direct compositions of opal glass with different types of materials.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	🏃	🚪	📶	📄	👤	
19,7	3000	3198	2426	505	407	110	332	M	O*	P*	Q*	-	-	7300

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80F10>72000 hodin

Watt: 19,7 W

Color temperature: 3000 K

Module luminous flux: 3198 lm

Luminaire luminous flux: 2426 lm

A: 505 mm

B: 407 mm

C: 110 mm

D: 332 mm

Dali 2: Available

Motion sensor: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 7300 g

Project 2



Lucis S0.K3.B50 BOWL LED / LDC (Polar)

Luminaire: Lucis S0.K3.B50 BOWL LED
Lamps: 1 x LED G6

