



FORUM ZL3.K2.O50.Y

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9006 structured

**Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
44,5	4000	6087	4684	500	90	2000	-	M	-	P*	Q*	-	5800

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 44,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 6087 lm

**Luminaire luminous flux:** 4684 lm

**A:** 500 mm

**B:** 90 mm

**C:** 2000 mm

: Not available

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Weight:** 5800 g

Lucis ZL3.K2.O50 FORUM LED / LDC (Polar)

Luminaire: Lucis ZL3.K2.O50 FORUM LED  
Lamps: 1 x LED G5

