


PIA S00.L1.P150.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | DALI 1 | DALI 2 | CORR | Corridor | Motion sensor | Bluetooth | Emergency module | PHASE CUT | Weight |
|---|------|-------------------------|----------------------------|-----|----|--------|--------|------|----------|---------------|-----------|------------------|-----------|--------|
| 4 | 3000 | 352 | 282 | 150 | 82 | - | - | - | - | - | - | - | S* | 700 |

Voltage: 230V

IK code: IK01

CRI: >80

LED life: L80/F10 50000 hours

Watt: 4 W

Color temperature: 3000 K

Module luminous flux: 352 lm

Luminaire luminous flux: 282 lm

A: 150 mm

B: 82 mm

Dali 1: Not available

Dali 2: Not available

Corridor function: Not available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Phase-cut dimming: Available on inquiry

Weight: 700 g

Lucis S00.L1.P150 PIA LED / LDC (Polar)

Luminaire: Lucis S00.L1.P150 PIA LED
Lamps: 1 x LED, 3000 K

