


FORUM PE PS43.K1.O50.Y PE

**Type:** ceiling and wall lamp

**Lampshade:** polyethylene opal PE

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
44,5	3000	5810	5340	500	430	90	20	M	O*	P*	Q*	-	3100

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 44,5 W

**Color temperature:** 3000 K

**Module luminous flux:** 5810 lm

**Luminaire luminous flux:** 5340 lm

**A:** 500 mm

**B:** 430 mm

**C:** 90 mm

**D:** 20 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 3100 g

Lucis PS43.K1.O50 PE FORUM PE LED / LDC (Polar)

Luminaire: Lucis PS43.K1.O50 PE FORUM PE LED  
Lamps: 1 x LED G5

