

POLARIS ZK ZK.P1.400.XY

Type: suspension lamp


Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

Colour: RAL chrom (77) 3 (77)

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 1	DALI 2	CORR	IK	EMER	BT	TR	Weight
26,2	3000	3904	3514	400	2000	L	M	N*	-	P*	Q*	-	5800

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >80

LED life: L80/F10 50000 hours

Watt: 26,2 W

Color temperature: 3000 K

Module luminous flux: 3904 lm

Luminaire luminous flux: 3514 lm

A: 400 mm

C: 2000 mm

Dali 1: Available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Weight: 5800 g

Lucis ZK.P1.400.X POLARIS ZK LED / LDC (Polar)

Luminaire: Lucis ZK.P1.400.X POLARIS ZK LED
Lamps: 1 x LED G5

