

POLARIS ZK ZK.P1.400.XY


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
25,5	3000	3784	3406	400	2000	M	-	P*	Q*	-	5800

Lucis ZK.P1.400.X POLARIS ZK LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 25,5 W

Color temperature: 3000 K

Module luminous flux: 3784 lm

Luminaire luminous flux: 3406 lm

A: 400 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 5800 g

Luminaire: Lucis ZK.P1.400.X POLARIS ZK LED
Lamps: 1 x LED G6

