


ALFA S00.L1.115.XY

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** painted steel plate RAL 9003 (.60) or RAL 9005 (.61)



| W | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | B   | DALI 1 | DALI 2 | CORR | IK | EMERGENCY | BLUETOOTH | PHASE CUT | Weight |
|---|------|-------------------------|----------------------------|-----|-----|--------|--------|------|----|-----------|-----------|-----------|--------|
| 4 | 3000 | 352                     | 264                        | 110 | 115 | -      | -      | -    | -  | -         | -         | S*        | 600    |

**Voltage:** 230V

**IK code:** IK01

**CRI:** >80

**LED life:** L80/F10 50000 hours

**Watt:** 4 W

**Color temperature:** 3000 K

**Module luminous flux:** 352 lm

**Luminaire luminous flux:** 264 lm

**A:** 110 mm

**B:** 115 mm

**Dali 1:** Not available

**Dali 2:** Not available

**Corridor function:** Not available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Phase-cut dimming:** Available on inquiry

**Weight:** 600 g

Lucis S00.L1.115.X ALFA LED / LDC (Polar)

Luminaire: Lucis S00.L1.115.X ALFA LED  
Lamps: 1 x LED 4027

