



CHARON PMMA S26.L2.CA2.Y

**Type:** ceiling and wall lamp

**Lampshade:** acrylic glass PMMA

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight g
16,2	4000	2564	1742	300	260	115	M	O*	-	Q*	-	1200

Lucis S26.L2.CA2 CHARON PMMA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 16,2 W

**Color temperature:** 4000 K

**Module luminous flux:** 2564 lm

**Luminaire luminous flux:** 1742 lm

**A:** 300 mm

**B:** 260 mm

**C:** 115 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1200 g

Luminaire: Lucis S26.L2.CA2 CHARON PMMA LED  
Lamps: 1 x LED G6

