




CHARON PMMA S44.L1.CA4.Y

Type: luminaire de plafond et mural
Abat-jour: verre acrylique PMMA
Luminaire: tôle en acier peint en blanc



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Emergency | Exit | Bluetooth | Track system | Weight |
|------|------|-------------------------------|----------------------------------|-----|-----|-----|-----------|-----------|------|-----------|--------------|--------|
| 37,1 | 3000 | 5628 | 4113 | 480 | 440 | 160 | M | O* | P* | Q* | - | 2600 |

Lucis S44.L1.CA4 CHARON PMMA LED / LDC (Polar)

Tension: 230V
IK code: IK06
Ballaste: Driver
CRI: >90
La vie de LED: L80/F10 50000 heures
Watt: 37,1 W
Température Couleur: 3000 K
Module luminous flux: 5628 lm
Luminaire luminous flux: 4113 lm
A: 480 mm
B: 440 mm
C: 160 mm
Dali 2: Disponible
Capteur de mouvement: Disponible sur demande
Module d'urgence: Disponible sur demande
Contrôle Bluetooth: Disponible sur demande
Track system: Non disponible
Sádrokarton: Non disponible
Poids: 2600 g

Luminaire: Lucis S44.L1.CA4 CHARON PMMA LED
 Lamps: 1 x LED G6

