




CHARON PMMA S44.L2.CA4.Y

**Type:** luminaire de plafond et mural  
**Abat-jour:** verre acrylique PMMA  
**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight
37,1	4000	6083	4523	480	440	160	M	O*	P*	Q*	- - 2600

Lucis S44.L2.CA4 CHARON PMMA LED / LDC (Polar)

**Tension:** 230V  
**IK code:** IK06  
**Ballaste:** Driver  
**CRI:** >90  
**La vie de LED:** L80/F10 50000 heures  
**Watt:** 37,1 W  
**Température Couleur:** 4000 K  
**Module luminous flux:** 6083 lm  
**Luminaire luminous flux:** 4523 lm  
**A:** 480 mm  
**B:** 440 mm  
**C:** 160 mm  
**Dali 2:** Disponible  
**Capteur de mouvement:** Disponible sur demande  
**Module d'urgence:** Disponible sur demande  
**Contrôle Bluetooth:** Disponible sur demande  
**Track system:** Non disponible  
**Sádrokarton:** Non disponible  
**Poids:** 2600 g

Luminaire: Lucis S44.L2.CA4 CHARON PMMA LED  
 Lamps: 1 x LED G6

