


CHARON PMMA S56.L1.CA6.Y

Typ: Decken- und Wandleuchte

Lampenschirm: Acrylglas PMMA

Leuchte: weiß lackiertes Stahlblech



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	0*	P*	Q*	-	-	4000
42,7	3000	6432	4632	600	560	175	M	O*	P*	Q*	-	-	4000

Lucis S56.L1.CA6 CHARON PMMA LED / LDC (Polar)

Spannung: 230V

IK Code: IK06

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 42,7 W

Farbtemperatur: 3000 K

Module luminous flux: 6432 lm

Luminaire luminous flux: 4632 lm

A: 600 mm

B: 560 mm

C: 175 mm

Dali 2: Verfügbar

Bewegungsmelder: Verfügbar auf Anfrage

Notlichtmodul: Verfügbar auf Anfrage

Bluetooth-Steuerung: Verfügbar auf Anfrage

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 4000 g

Luminaire: Lucis S56.L1.CA6 CHARON PMMA LED
Lamps: 1 x LED G6

