




CHARON PMMA S56.L1.CA6.Y

**Type:** luminaire de plafond et mural  
**Abat-jour:** verre acrylique PMMA  
**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Exit	Bluetooth	Track system	Weight
42,7	3000	6432	4632	600	560	175	M	O*	P*	Q*	-	4000

Lucis S56.L1.CA6 CHARON PMMA LED / LDC (Polar)

**Tension:** 230V  
**IK code:** IK06  
**Ballaste:** Driver  
**CRI:** >90  
**La vie de LED:** L80/F10 50000 heures  
**Watt:** 42,7 W  
**Température Couleur:** 3000 K  
**Module luminous flux:** 6432 lm  
**Luminaire luminous flux:** 4632 lm  
**A:** 600 mm  
**B:** 560 mm  
**C:** 175 mm  
**Dali 2:** Disponible  
**Capteur de mouvement:** Disponible sur demande  
**Module d'urgence:** Disponible sur demande  
**Contrôle Bluetooth:** Disponible sur demande  
**Track system:** Non disponible  
**Sádrokarton:** Non disponible  
**Poids:** 4000 g

Luminaire: Lucis S56.L1.CA6 CHARON PMMA LED  
 Lamps: 1 x LED G6

