




CHARON PMMA S56.L2.CA6.Y

Type: ceiling and wall lamp

Lampshade: acrylic glass PMMA

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight g |
|------|------|-------------------------|----------------------------|-----|-----|-----|--------|---------------|------------------|-----------|--------------|----------|
| 42,7 | 4000 | 6952 | 4871 | 600 | 560 | 175 | M | O* | P* | Q* | - | 4000 |

Lucis S56.L2.CA6 CHARON PMMA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 42,7 W

Color temperature: 4000 K

Module luminous flux: 6952 lm

Luminaire luminous flux: 4871 lm

A: 600 mm

B: 560 mm

C: 175 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 4000 g

Luminaire: Lucis S56.L2.CA6 CHARON PMMA LED
Lamps: 1 x LED G6

