




CHARON IP44 PS43.L2.T15.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight
32	4000	5214	3543	500	430	145 Project 1	M	O*	P*	0*	-

Operator
Telephone
Fax
e-Mail

DIALUX
11.00.2024

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 32 W

Color temperature: 4000 K

Module luminous flux: 5214 lm

Luminaire luminous flux: 3543 lm

A: 500 mm

B: 430 mm

C: 145 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 5900 g

Lucis PS43.L2.T15 CHARON LED / LDC (Polar)

Luminaire: Lucis PS43.L2.T15 CHARON LED
Lamps: 1 x LED G6

