


ZERO ZL3.K1.Z415.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9006 structured

Pendant: steel wire suspension with a transparent cable



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 1 | DALI 2 | CORR | ☺ | ☒ | BT | 📄 | 👤 |
|----|------|-------------------------|----------------------------|-----|----|------|--------|--------|------|---|----|----|---|------|
| 36 | 3000 | 4448 | 3467 | 415 | 80 | 2000 | - | M | N* | - | P* | Q* | - | 4700 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 36 W

Color temperature: 3000 K

Module luminous flux: 4448 lm

Luminaire luminous flux: 3467 lm

A: 415 mm

B: 80 mm

C: 2000 mm

Dali 1: Not available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Weight: 4700 g

Lucis ZL3.K1.Z415 ZERO LED / LDC (Polar)

Luminaire: Lucis ZL3.K1.Z415 ZERO LED
Lamps: 1 x LED G5

