



ZERO ZL3.K2.Z415.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9006 structured

Pendant: steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CORR	Handicap	Bluetooth	Emergency	Weight
36	4000	4659	3631	415	80	2000	-	M	N*	-	P*	Q*	4700

Voltage: 230V

IK code: IK01

ballast: EVG

CRI: >90

LED life: L80/F10 50000 hours

Watt: 36 W

Color temperature: 4000 K

Module luminous flux: 4659 lm

Luminaire luminous flux: 3631 lm

A: 415 mm

B: 80 mm

C: 2000 mm

Dali 1: Not available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Weight: 4700 g

Lucis ZL3.K2.Z415 ZERO LED / LDC (Polar)

Luminaire: Lucis ZL3.K2.Z415 ZERO LED
Lamps: 1 x LED G5

