




CHARON S29.L2.T135.Y

Type: luminaire de plafond et mural

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: tôle en acier peint en blanc

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight
21,3	4000	3476	2400	360	290	130	M	O*	P*	Q*	- - 2800

Lucis S29.L2.T135 CHARON LED / LDC (Polar)

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 21,3 W

Température Couleur: 4000 K

Module luminous flux: 3476 lm

Luminaire luminous flux: 2400 lm

A: 360 mm

B: 290 mm

C: 130 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2800 g

Luminaire: Lucis S29.L2.T135 CHARON LED
Lamps: 1 x LED G6

