

POLARIS ZL ZL1.P2.500.XY




**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL chrom (.77) or chrome (.80)

**Pendant:** steel wire suspension with a transparent cable

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
37,3	4000	6096	5486	500	2000	M	-	P*	Q*	R*	7700

Lucis ZL1.P2.500.X POLARIS ZL LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 37,3 W

**Color temperature:** 4000 K

**Module luminous flux:** 6096 lm

**Luminaire luminous flux:** 5486 lm

**A:** 500 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Not available

**Weight:** 7700 g

Luminaire: Lucis ZL1.P2.500.X POLARIS ZL LED  
Lamps: 1 x LED G6

