

POLARIS ZK PE ZK.P1.630.XY PE


**Type:** suspension lamp

**Lampshade:** polyethylene opal PE

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

**Pendant:** white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 1	DALI 2	CORR	IK10	IP20	Bluetooth	Emergency	Weight
53,6	3000	7416	6823	630	2000	L	M	N*	-	P*	Q*	-	8700

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >80

**LED life:** L80/F10 50000 hours

**Watt:** 53,6 W

**Color temperature:** 3000 K

**Module luminous flux:** 7416 lm

**Luminaire luminous flux:** 6823 lm

**A:** 630 mm

**C:** 2000 mm

**Dali 1:** Available

**Dali 2:** Available

**Corridor function:** Available on inquiry

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Weight:** 8700 g

Lucis ZK.P1.630.X PE POLARIS ZK PE LED / LDC (Polar)

Luminaire: Lucis ZK.P1.630.X PE POLARIS ZK PE LED  
Lamps: 1 x LED G5

