

POLARIS ZL PE ZL1.P1.400.XY PE

**Type:** suspension lamp

**Lampshade:** polyethylene opal PE

**Metal parts:** painted steel plate RAL 9003 (.31), RAL chrom (.77) or chrome (.80)

**Pendant:** steel wire suspension with a transparent cable

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight	
25,5	3000	3784	3482	400	2000	M	-	P*	Q*	R*	D*	4100

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 25,5 W

**Color temperature:** 3000 K

**Module luminous flux:** 3784 lm

**Luminaire luminous flux:** 3482 lm

**A:** 400 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 4100 g

Lucis ZL1.P1.400.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P1.400.X PE POLARIS ZL PE LED  
Lamps: 1 x LED G6

