

POLARIS ZL PE ZL1.P1.630.XY PE




Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

Suspension: câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	☼	☼	☼	☼	☼	☼
53,6	3000	7416	6823	630	2000	M	-	P*	Q*	R*	-	8700

Tension: 230V

Ballaste: Driver

IK code: IK10

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 53,6 W

Température Couleur: 3000 K

Module luminous flux: 7416 lm

Luminaire luminous flux: 6823 lm

A: 630 mm

C: 2000 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Disponible sur demande

Sádrokarton: Non disponible

Poids: 8700 g

Lucis ZL1.P1.630.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P1.630.X PE POLARIS ZL PE LED
Lamps: 1 x LED G5

