

POLARIS ZL PE ZL1.P2.630.XY PE




Type: suspension lamp







Lampshade: polyethylene opal PE

Metal parts: painted steel plate RAL 9003 (.31), RAL chrom (.77) or chrome (.80)

Pendant: steel wire suspension with a transparent cable

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C							
53,6	4000	7840	7213	630	2000	M	–	P*	Q*	R*	–	8700

Voltage: 230V

Ballast: Driver

IK code: IK10

CRI: >90

LED life: L80/F10 50000 hours

Watt: 53,6 W

Color temperature: 4000 K

Module luminous flux: 7840 lm

Luminaire luminous flux: 7213 lm

A: 630 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8700 g

Lucis ZL1.P2.630.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.630.X PE POLARIS ZL PE LED
Lamps: 1 x LED G5

