


CHARON PMMA S33.L3.CA3.Y

**Type:** ceiling and wall lamp

**Lampshade:** acrylic glass PMMA

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
16	3000	2412	1619	375	330	135	M	O*	P*	Q*	-	1900

Lucis S33.L3.CA3 CHARON PMMA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 16 W

**Color temperature:** 3000 K

**Module luminous flux:** 2412 lm

**Luminaire luminous flux:** 1619 lm

**A:** 375 mm

**B:** 330 mm

**C:** 135 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1900 g

Luminaire: Lucis S33.L3.CA3 CHARON PMMA LED  
Lamps: 1 x LED G6

