


OMNIA o.1250.K2.X

**Type:** floor lamp

**Lampshade:** acrylic glass

**Metal parts:** painted steel plate RAL 9003 (.60), RAL 9005 (.61) or RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CDRR	Emergency	Motion sensor	Bluetooth	Track system	Weight
9,6	4000	1295	1005	400	250	1250	-	-	-	-	-	-	-	8500

**Voltage:** 230V

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 9,6 W

**Color temperature:** 4000 K

**Module luminous flux:** 1295 lm

**Luminaire luminous flux:** 1005 lm

**A:** 400 mm

**B:** 250 mm

**C:** 1250 mm

**Dali 1:** Not available

**Dali 2:** Not available

**Corridor function:** Not available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Weight:** 8500 g

Lucis O.1250.K2.X OMNIA LED / LDC (Polar)

Luminaire: Lucis O.1250.K2.X OMNIA LED  
Lamps: 1 x LED G5

