



OMNIA O.525.K2.X

Type: luminaire de table

Abat-jour: verre acrylique

Les pièces métalliques: acier laqué RAL 9003 (.60), RAL 9005 (.61) ou RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CDRR	Corridor	Movement	Bluetooth	Emergency	Weight
9,6	4000	1295	1005	395	190	525	-	-	-	-	-	-	-	2700

Tension: 230V

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 9,6 W

Température Couleur: 4000 K

Module luminous flux: 1295 lm

Luminaire luminous flux: 1005 lm

A: 395 mm

B: 190 mm

C: 525 mm

Dali 1: Non disponible

Dali 2: Non disponible

fonction Corridor: Non disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Non disponible

Track system: Non disponible

Poids: 2700 g

Lucis O.525.K2.X OMNIA LED / LDC (Polar)

Luminaire: Lucis O.525.K2.X OMNIA LED
Lamps: 1 x LED G5

