



DAPHNE ZL ZL3.L1.D551.31Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL chrom (.77)

Pendant: wire suspension with white cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	IK10	IK15	Bluetooth	Emergency	Weight
37,1	3000	5628	4247	550	245	2000	max. 1000	M	-	P*	Q*	-	7700

Lucis ZL3.L1.D551.X DAPHNE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 37,1 W

Color temperature: 3000 K

Module luminous flux: 5628 lm

Luminaire luminous flux: 4247 lm

A: 550 mm

B: 245 mm

C: 2000 mm

D: max. 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 7700 g

Luminaire: Lucis ZL3.L1.D551.X DAPHNE LED
Lamps: 1 x LED G6

