

POLARIS ZT PE ZT.P2.400.XY PE

**Type:** luminaire suspendu

**Abat-jour:** polyéthylène opal PE

**Les pièces métalliques:** acier laqué RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chromé (.80), inox (.83) ou laiton (.84)

**Suspension:** tube

The luminaire driver is placed right inside the luminaire (LED version).



| W    | K    | Module<br>luminous<br>flux lm | Luminaire<br>luminous<br>flux lm | A   | C    | DALI<br>2 | 🚶 | 🚶➡ | 📶  | 📄  | 👤 |      |
|------|------|-------------------------------|----------------------------------|-----|------|-----------|---|----|----|----|---|------|
| 25,5 | 4000 | 4096                          | 3769                             | 400 | 1000 | M         | - | P* | Q* | R* | - | 4400 |

**Tension:** 230V

**Ballaste:** Driver

**IK code:** IK10

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 25,5 W

**Température Couleur:** 4000 K

**Module luminous flux:** 4096 lm

**Luminaire luminous flux:** 3769 lm

**A:** 400 mm

**C:** 1000 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Disponible sur demande

**Sádrokarton:** Non disponible

**Poids:** 4400 g

Lucis ZT.P2.400.X PE POLARIS ZT PE LED / LDC (Polar)

Luminaire: Lucis ZT.P2.400.X PE POLARIS ZT PE LED  
Lamps: 1 x LED G6

