


IZAR III ZLI3.L2.600.XY

Type: suspension lamp

Lampshade: acrylic glass, front white (.92) or black (.93)

Metal parts: white painted steel plate

Pendant: steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
20,9	4000	2806	2573	600	80	2000	40	M	-	P*	Q*	R*	D* 1900

Lucis ZLI3.L2.600.X IZAR III LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 20,9 W

Color temperature: 4000 K

Module luminous flux: 2806 lm

Luminaire luminous flux: 2573 lm

A: 600 mm

B: 80 mm

C: 2000 mm

D: 40 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 1900 g

Luminaire: Lucis ZLI3.L2.600.X IZAR III LED
Lamps: 1 x LED G6

