



ELIOS ZK.K1.E120.XY

**Type:** suspension lamp

**Lampshade:** acrylic glass for LED

**Metal parts:** painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)

**Pendant:** transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
9,6	3000	1237	1001	120	135	1500	M	-	P*	Q*	R*	D* 1100

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 9,6 W

**Color temperature:** 3000 K

**Module luminous flux:** 1237 lm

**Luminaire luminous flux:** 1001 lm

**A:** 120 mm

**B:** 135 mm

**C:** 1500 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 1100 g

Lucis ZK.K1.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis ZK.K1.E120.X ELIOS LED  
Lamps: 1 x LED G5

