


**RONDO IP44 PS13.K1.R550.Y**

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☺	☺	☺	☺	☺	☺
36	3000	4448	3021	550	342	83	13	M	-	-	Q*	-	-	6500

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 36 W

**Color temperature:** 3000 K

**Module luminous flux:** 4448 lm

**Luminaire luminous flux:** 3021 lm

**A:** 550 mm

**B:** 342 mm

**C:** 83 mm

**D:** 13 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 6500 g

Lucis PS13.K1.R550 RONDO LED / LDC (Polar)

Luminaire: Lucis PS13.K1.R550 RONDO LED  
Lamps: 1 x LED G5

