


ZERO IP44 PS13.K1.Z600.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | ☺ | ☺ | ☺ | ☺ | ☺ | ☺ |
|------|------|-------------------------------|----------------------------------|-----|-----|-----|----|-----------|----|----|----|---|---|------|
| 50,8 | 3000 | 6658 | 5188 | 600 | 480 | 100 | 13 | M | O* | P* | Q* | - | - | 8200 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 50,8 W

Color temperature: 3000 K

Module luminous flux: 6658 lm

Luminaire luminous flux: 5188 lm

A: 600 mm

B: 480 mm

C: 100 mm

D: 13 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 8200 g

Lucis PS13.K1.Z600 ZERO LED / LDC (Polar)

Luminaire: Lucis PS13.K1.Z600 ZERO LED
Lamps: 1 x LED G5

